

Product Information



FOAM-KLOR CHLORINATED SELF-FOAMING DETERGENT

CLEANS

- Tank exteriors
- Floors
- Conveyors
- Other environmental surfaces

FEATURES/BENEFITS

- Self-Foaming – generates copious, stable foam
 - No foam additives needed
 - Increased dwell time to penetrate, dislodge and suspend difficult soils
 - Ideal for use in air operated and hand held foam units
- Complex blend of surfactants – providing maximum detergency
- Chlorinated
 - Aids in the removal of protein soils
 - Removes “bluing” from stainless steel surfaces
 - Effectively controls odors
 - Helps control mold and mildew
- Free rinsing – leaves no residue
- Effective in hard water conditions
- Environmentally friendly – phosphate free, biodegradable

DESCRIPTION

- FOAM-KLOR is a liquid, self-foaming, chlorinated alkaline detergent, designed for use as an exterior surface cleaner. FOAM-KLOR has been formulated to rapidly penetrate, dislodge and suspend all the soils typically found in the brewing environment.

USE DIRECTIONS

- For foam cleaning applications use a dilution of approximately 2 - 6 ounces of FOAM-KLOR to each gallon of hot water, or as required.
- For manual cleaning use ½ to 4 ounces of FOAM-KLOR per gallon of warm water.

The information contained herein is to our knowledge, true and accurate. Because conditions of use are beyond our control, we make no warranty or representation, expressed or implied, except that the products discussed herein conform to the chemical descriptions shown on their labels. Nothing contained herein should be construed as permission or recommendation to infringe any patent. No agent, representative, or employee of this company is authorized to vary any items of the notice.

Ace Chemical Products, Inc. • Milwaukee, Wisconsin 53224 • 1-800-248-8515 • brewcitysolutions.com

Product Information



FOAM-KLOR

USE DIRECTIONS (continued)

- For high pressure cleaning use 1/2 to 2 ounces FOAM-KLOR to each gallon of water.
- For specific use recommendations, or answers to any cleaning or sanitation questions you may have, contact us at 1-800-248-8515.

TECHNICAL DATA

FORM	Liquid
COLOR	Colorless
ODOR	Slight chlorine
POUNDS PER GALLON	9.2
pH of a 1% SOLUTION	> 12
HYPOCHLORITE	500 ppm at a 1:40 dilution
FOAMING	High
BIODEGRADABLE	Complete
COMPATIBILITY	Avoid soft metals

5060-L03-js

Always observe label precautionary statements and follow the information provided in our Material Safety Data Sheet for this product. A safety video presentation is available on request.

The information contained herein is to our knowledge, true and accurate. Because conditions of use are beyond our control, we make no warranty or representation, expressed or implied, except that the products discussed herein conform to the chemical descriptions shown on their labels. Nothing contained herein should be construed as permission or recommendation to infringe any patent. No agent, representative, or employee of this company is authorized to vary any items of the notice.

Ace Chemical Products, Inc. • Milwaukee, Wisconsin 53224 • 1-800-248-8515 • brewcitysolutions.com